

ASSEMBLY INSTRUCTIONS:

Product Code : CHOICE-BK

Product Name: Choice Task Chair

TIME REQUIRED:

10 minutes

TOOLS REQUIRED:

Screwdriver, Electric Drill, Pencil, Measuring tape/Ruler

*Tools are not included.

SKILL REQUIRED:

Easy  Hard

The Assembly Skill Rating is a 5-point system that shows the degree of effort needed in assembling a specific product. With 1 being easy for the average person and 5 requiring an expert. For most products, two persons are recommended.

Please note, as this is a commercial product, some intermediate skills are required.

*No pre-drill holes or markings are provided on tops.

NOTE

- As this is a commercial product, some intermediate skills may be required.
 - No pre-drill holes or markings are provided on our table or desk tops.
 - Please check you have all hardware before assembling.
- If you are missing any hardware, please contact your Rapidline reseller. Please ensure you have the name of the item, required hardware part and quantity.
 - Please retain your receipt as proof of purchase to validate your warranty.
- Assemble on a clean, flat, smooth surface such as a rug or carpet to avoid parts from being scratched.
 - Remove all wrapping materials, including staples and packing straps before you start to assemble
 - Keep all hardware parts out of reach of children.







CAUTION

- Heavy product. Do not attempt to lift or move without help
- Do not tighten screws and bolts until completely assembled.
- Do not use this product unless all bolts and screws are firmly secured and tightened.

WARNING


- If parts are missing, broken, damaged or worn stop using the product until all repairs are made.
 - Failure to follow these warnings could result in serious injury.

CHOICE

			
A. Back	B. Seat	C. Castors	D. Plastic Lug
			
E. Bellows	F. Gas lift		



- | | | |
|--|---|---|
| <p>1.</p> <ul style="list-style-type: none"> • Insert gas lift into the base with castors • Place the bellows over the gas lift and press down | <p>2.</p> <ul style="list-style-type: none"> • Fit the seat on top of the gas lift | <p>3.</p> <ul style="list-style-type: none"> • Slide the bar of the back into the insert slot of the mechanism at the back of seat, but first pull out the plastic lug then slide the bar in |
|--|---|---|

- | | |
|--|---|
|  | <p>4.</p> <ul style="list-style-type: none"> • Place the plastic lug back into place • Tighten the knob once reached the desired height |
|--|---|

